

Cristal-Flo™ II

Aboveground Sand Filter System

by Sta-Rite®



Maximum capacity, minimum maintenance and cost

Add sparkle to your aboveground pool and spend less time maintaining it. Sand media is a long-established method of pool water filtration and Sta-Rite® raised the bar with its Cristal-Flo™ II sand system.

- Great performance and efficiency. The filter tank requires minimum maintenance. A simple turn of the multi-port valve lever accomplishes routine backwashing.
- The tank's sophisticated design, internal components and even hydraulics have been engineered to maximize filter performance and extend time between cleanings.
- Unionized pump to filter connection allows for easy installation and servicing.
- Combination water and sand drain makes servicing and winterizing fast and easy.
- The JWP pump features precision-manufactured components, rugged construction and a continuous duty, smooth running motor for years of quiet, dependable service.

Cristal-Flo™ II

Aboveground Sand Filter System



- Multiport valve selector activates backwashing action with one quick turn.
- Easy-to-read top-mounted pressure gauge.
- One-piece polyethylene tank will never corrode.
- Available with JWP or ABG pump options.



The low cost, easy-to-maintain filter system

Cristal-Flo™ II aboveground sand filter systems offer a variety of pump and filter combinations that allow you to precision-match your system to almost any pool requirement. Everything is easily assembled on a attractive, robust platform. And nothing could be easier to operate or maintain—a simple twist of the wrist puts the Cristal-Flo II filter system in backwash mode for quiet, efficient cleaning action.

Economical

The sand filtration media is permanent—no need to replace cartridge-style elements.

Built to last

The Cristal-Flo II filter tank and internal components are constructed of heavy-duty polyethylene, and the pump is made of Sta-Rite's exclusive Dura-Glas™ composite resin. This system won't corrode and resists the elements for years of service.

Filter Performance

Model	Turnover Capacity (Gal.) 8 Hours	Filter Area (Sq. Ft.)	Pump (HP)	Sand Required ¹ (lbs.)
SRCF2016AN*	16,000	1.4	1	100
SRCF2019AE*	19,000	1.8	1	150
SRCF2019JE	19,000	1.8	1	150
SRCF2019JN	19,000	1.8	1	150
SRCF2019JO	19,000	1.8	1½	150
SRCF2022JE	28,000	2.3	1	250
SRCF2022JF	28,000	2.3	1½	250
SRCF2022JO	28,000	2.3	1½	250

¹Use only #20 white quartz silica sand, size range .40–.55mm; 12"–15" sand bed depth required.

*Utilize ABG pump.

One-year limited warranty. See warranty for details.

Available from:



Simply Smarter.

www.staritepool.com

Phone: 800-831-7133

pumps / filters / heaters / heat pumps / automation / lighting / cleaners / sanitizers / water features / maintenance products