

Jandy[®] Aqua Accent

Installation Manual

Jandy[®]



Jandy Aqua Accent Installation Manual

All Aqua Accents should be installed on the tile or face of a wall. It is not recommended that these items be installed in concrete, thin set or grout, as expansion and contraction can cause cracks or separations.

TOOLS REQUIRED

- a) Hacksaw or pipe cutting tool
- b) Exterior grade silicon adhesive or similar construction adhesive or epoxy
- c) Tape measure
- d) 1" drill bit (for Sconces only)

PLUMBING REQUIREMENT

- a) $\frac{3}{4}$ " PVC pipe

b) Plumbing should be installed through the wall of the pool or fountain in the exact location for the installation of the Aqua Accent. Please note: Each of the Aqua Accents can be installed either in the pipe socket in the back of the unit or can be installed in the cavity of the product. This provides more flexibility in the pipe location and in assuring that multiple units can be installed evenly on the wall.

c) A valve should be installed on each plumbing line to the Aqua Accents. If multiple Accents are installed, separate valves need to be installed in positions that allow individual adjustment.

INSTALLATION - ALL ACCENTS EXCEPT SCONCES

Place Aqua Accent on the wall over the pipe. Measure and align the Accent and mark the exact location. (Please note: plumbing can either be installed in the pipe socket or in the cavity behind the Aqua Accent.) Measure the pipe length from the wall to the socket and make the appropriate cut. A guideline for each of the units is shown below along with dimensions and weights. If the pipe is going to discharge into the cavity behind the accent, cut pipe to assure proper flow into the cavity. When making a cavity installation the adhesive around the flange must be continuous to avoid leakage. Apply a continuous bead of silicon, or similar adhesive around the rear flange of the Aqua Accent. Install on the wall over the pipe and align. Remove any excess adhesive. If the pipe is installed in the socket, apply silicon to the pipe and in the hole of the Accent. Make sure to use a smooth tool to remove the excess in and around the water exit hole to assure proper water flow through the mouth. The adhesive should hold the Aqua Accent in place. In the event the unit does not stay secure, apply tape or similar means to the unit. Once the adhesive is dry, the Aqua Accent will be secure.



NOTE: The pipe can be installed in either the pipe socket located in the back of the Aqua Accent or the pipe can discharge the water into the cavity in the back and then flow out of the mouth. If discharging water into the cavity, the adhesive must be applied in a continuous bead around the flange of the unit.

SCONCE INSTALLATION

Installing a sconce requires a slightly different installation technique. First, align the sconce and mark where the pipe needs to penetrate the back. Next, drill a pipe installation hole using the 1" drill bit. (NOTE: It is preferred that the hole is as low on the back as possible to help level the water flow. In the event this is not possible, allow enough room in the unit and then cut the pipe to allow for a $\frac{3}{4}$ " 90 degree elbow to be installed. Apply the silicon in a continuous bead around the back of the sconce and around the pipe hole. Install the sconce, align and then install additional adhesive around the pipe hole. Make sure to wipe off all excess adhesive. Allow the adhesive to dry and the unit is ready to be started.

Jandy Aqua Accent Installation Manual



#2001 Neptune



#2010 Expression



#2050 Baroque Med.



#2060 Baroque Lg.



#2410 Baroque XL



#2080 Roman



#2090 Victorian



#2100 Renaissance



#2120 Sun



#2130 Regal



#2150 Circle/Leaves



#2160 Fluted



#2170 4 Point



#2180 Scalloped



#2190 Sunflower Sm.



#2200 Sunflower Lg.



#2210 Star Sm.



#2220 Star Med.



#2230 Oak Leaf



#2240 Art Deco



#2250 Chanterelle



#2260 Round



#2270 Square Fern



#2280 Square Dahlia



#2300 Fleur de lis



#2310 Versailles



#2320 Bastion




#2330 Gothic

Jandy Aqua Accent Installation Manual



#2400 Conch



#2410 Nautilus



#2420 Fossil Nautilus



#2430 Shell Hand Hold

| Series # | Description | Size | Weight (lbs.) | Dimensions | Pipe Length | Pipe Location (down from center) |
|----------|---------------------------|----------|---------------|-------------|-------------|----------------------------------|
| 2001 | Neptune | Large | 3.50 | 10½" x 11¼" | 1¾" | 2½" |
| 2010 | Expression | Small | 0.75 | 4" x 5" | 1" | 1¼" |
| 2050 | Lion, Baroque | Medium | 1.50 | 7½" x 9" | 2" | 1¼" |
| 2060 | Lion, Baroque | Large | 2.20 | 10½" x 12" | 2" | 1" |
| 2070 | Lion, Baroque | Ex Large | 8.00 | 13½" x 18" | 2¾" | 3¼" |
| 2080 | Lion, Roman | Medium | 2.25 | 8½" x 10½" | 1½" | 1¾" |
| 2090 | Lion, Victorian | Small | 1.35 | 6½" x 7" | 1¾" | 1" |
| 2100 | Lion, Renaissance | Small | 1.25 | 8" x 8" | 1¼" | 1½" |
| 2120 | Lion, Sun | Medium | 2.25 | 9" x 9" | 1¼" | 1½" |
| 2130 | Lion, Regal | Large | 3.75 | 9" x 12½" | 1½" | 2" |
| 2150 | Rosette, Circle of leaves | Small | 0.80 | 7" x 7" | ¾" | Center |
| 2160 | Rosette, Fluted | Medium | 1.00 | 8" x 8" | 1" | Center |
| 2170 | Rosette, 4-point | Small | 0.80 | 6" x 6" | ¾" | Center |
| 2180 | Rosette, Scalloped | Medium | 1.00 | 8" x 8" | 7/8" | Center |
| 2190 | Rosette, Sunflower | Small | 1.20 | 8" x 6¼" | 7/8" | Center |
| 2200 | Rosette, Sunflower | Large | 2.50 | 14" x 11½" | 1¾" | Center |
| 2210 | Rosette, Star | Small | 0.50 | 4½" x 4½" | ½" | Center |
| 2220 | Rosette, Star | Medium | 1.00 | 6¾" x 6¾" | ¾" | Center |
| 2230 | Rosette, Oak Leaf | Small | 0.50 | 4½" x 4½" | ¾" | Center |
| 2240 | Rosette, Art Deco | Small | 1.25 | 5¼" x 5¼" | 1" | Center |
| 2250 | Rosette, Chanterelle | Medium | 1.00 | 6" x 8" | ¾" | Center |
| 2260 | Rosette, Round | Medium | 1.50 | 8½" DIA. | ¾" | Center |
| 2270 | Rosette, Square Fern | Large | 2.50 | 10½" x 10½" | ½" | Center |
| 2280 | Rosette, Square Dahlia | Large | 2.50 | 10½" x 10½" | ¾" | Center |
| 2300 | Sconce, Fleur de lis | Large | 9.00 | 21" x 12" | ¾" | 2" |
| 2310 | Sconce, Versailles | Large | 6.00 | 16" x 11½" | ¾" | Up 1½" |
| 2320 | Sconce, Bastion | Medium | 2.50 | 12½" x 6" | ¾" | ½" |
| 2330 | Sconce, Gothic | Medium | 2.50 | 12½" x 6" | ¾" | ½" |
| 2400 | Shell, Conch | Small | 1.00 | 5½" x 6½" | ½" | Right 1" |
| 2410 | Shell, Nautilus | Small | 1.00 | 3" x 6" | ½" | 1¼" |
| 2420 | Shell, Fossil Nautilus | Medium | 1.75 | 8½" x 7" | ¾" | 1" |
| 2430 | Shell, Hand Hold | Small | 0.75 | 7" x 5½" | N/A | N/A |

Aqua Accent Limited Warranty

Aqua Accent Limited Warranty

The Limited Warranty is extended to the original purchaser of the Aqua Accent, manufactured by Splash Technologies, Inc., 1342 South Powerline Road, Deerfield Beach, Florida 33442.

Splash Technologies warrants this product it manufactures, including all parts and components thereof, to be free of defects in material and workmanship for a period of twelve months. The Limited Warranty does not apply if the failure is caused or contributed by any of the following: improper handling, improper storage, abuse, improper installation, unsuitable application of the unit, lack of reasonable and necessary maintenance, or repairs made or attempted by other than authorized service centers or technicians. Splash Technologies will repair or replace, at its option, a unit proved to be defective within the warranty period and under the conditions of the warranty.

Splash Technologies is not responsible for the cost of removal of the unit, damages due to removal or installation, any shipping charges to or from the factory, or the installation of a repaired or replacement unit.

Implied Warranties, when applicable, shall commence upon the same date as the Express Warranty provided above, and shall, except for warranties of title extended only for the duration of the Express Warranty. Some states do not allow limitations on how long an implied warranty lasts. So the above limitation may not apply to you. The only remedy provided to you under an applicable implied warranty and the Express Warranty shall be the remedy provided under the Express Warranty. Subject to the terms and conditions contained therein, Splash Technologies, shall not be liable for incidental and consequential losses and damages under the Express Warranty, and applicable implied warranty, or claims for negligence, except to the extent that this limitation is found to be unenforceable under the applicable state law. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusion may not apply to you. The Warranty gives you specific legal rights and you may also have other rights which vary from state to state.

Warranty Registration Card

As a necessary precondition to warranty coverage, return this card within 15 days of product purchase date

Name: _____

Company: _____

Address: _____

Bus. Phone: _____

Bus. Fax: _____

Splash Product: _____

Mfg Date: _____

Distributor: _____

Date Purchased: _____

Splash Technologies, Inc. 1342 South Powerline Road Deerfield Beach, Florida 33442