

Posi-Flo® II

Cartridge Filters

by Sta-Rite®



Removing particles you can't even see

How clean and clear will the Posi-Flo® II cartridge filter keep your water? How about so clean that particles half as big as your eye can see are removed (20 microns)? And that includes gel-like particles from suntan and body oils, as well as sand, dirt and leaves. What's more, the filter element in Posi-Flo II holds more dirt than others of the same size. The secret is a balanced-flow hydraulic design that directs water equally over the entire surface area of the element so it can hold more dirt before it needs cleaning. Other key features include:

- Precision-molded fiberglass-reinforced thermoplastic tank that will never corrode and delivers years and years of dependable service.
- Continuous internal air bleed tube with protective screen helps assure water is properly dispersed across the media for consistent dirt-trapping performance.

- Top and bottom clamps for ease of service and simple, safe and secure closure.
- Bottom end cap on the element seals into tank base for extra strength and easy positioning after cleaning.
- Clamp knob is molded plastic with brass insert that prevents over-tightening.



Tough, pleated polyester filter element traps particles as small as 20 microns and provides huge surface area in a very compact unit.

Posi-Flo® II Cartridge Filters



Top-mounted pressure gauge positioned for easy reading

Simple clamping system for fast access to filter element

Fiberglass-reinforced thermoplastic tank will not corrode and withstands all the elements



Highest dirt-loading capacity in its class

Posi-Flo® II cartridge filter has great respect for your time. It captures more dirt between cleanings than any other in its size class, so you'll clean it less often. And when it's time to clean, it's a snap. Just open the tank, remove the element and rinse it off with your garden hose.*

A versatile performer

The Posi-Flo II is available in a wide range of sizes and flow rates. Whether residential or commercial, indoor or outdoor, there's a model that's perfect for your pool or spa.

Simple to service

The two-point tank disassembly provides fast access to the filter element and the rest of the unit. And the stainless steel, corrosion-resistant clamps are precision engineered for fast element removal and replacement.

*Cartridges used in conjunction with certain pool/spa sanitizers may require soaking in special cleaning solutions.

Filter Performance

Model	For Pools Up to (Gal.) 8 Hr. Turnover	Filter Area (Sq. Ft.)	Flow Rated at 1 GPM per Sq. Ft.
PTM50	24,000	50	50
PTM70	34,000	70	70
PTM100	48,000	100	100
PTM135	65,000	135	135

Operating Limits—Maximum continual operating pressure is 50 PSI. For Pool/Spa (bather) applications, the maximum operating water temperature within the filter is 104°F (40°C).

One-year limited warranty. See warranty for details.

Available from:



Simply Smarter.

www.staritepool.com

Phone: 800-831-7133 Fax: 800-284-4151



pumps / filters / heaters / heat pumps / automation / lighting / cleaners / sanitizers / water features / maintenance products